

4-Way CASSETTE



700x700mm panel design



Built-in high head drain pump



Pre-set fresh air inlet



Quiet operation



4-Way CASSETTE



HW-BA116ABK



YR-E17A



HW-BA101ABT



YR-E16B



YR-HRS01

Model/Indoor unit			AB052MCERA	AB072MCERA	AB092MCERA	AB122MCERA	AB162MCERA	AB182MCERA(C)
Capacity	Cooling	kBtu/h	5.1	7.5	9.5	12.3	15.3	19.1
		kW	1.5	2.2	2.8	3.6	4.5	5.6
	Heating	Btu/h	5.8	8.5	10.9	13.6	17.1	21.5
		kW	1.7	2.5	3.2	4	5	6.3
Electrical Parameters	Power supply	PhV/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
	Air flow (H)	m ³ /h	650/540/430	700/590/480	700/590/480	700/590/480	700/590/480	700/590/480
Performance	Sound pressure level(H/M/L)	dB(A)	31/29/28	32/30/29	32/30/29	32/30/29	33/30/29	33/30/29
	Sound power level(H/M/L)	dB(A)	45/43/42	46/44/43	46/44/43	46/44/43	47/44/43	47/44/43
	External dimensions(W/D/H)	mm	570/570/260	570/570/260	570/570/260	570/570/260	570/570/260	570/570/260
Installation	Shipping dimensions(W/D/H)	mm	718/680/380	718/680/380	718/680/380	718/680/380	718/680/380	718/680/380
	Net/Shipping weight	kg	16/19	16/19	16/19	19/22	19/22	19/22
	Refrigerant liquid pipe	mm	6.35	6.35	6.35	6.35	6.35	6.35
	Refrigerant gas pipe	mm	9.52	9.52	9.52	12.7	12.7	12.7
	Model name		PB-700IB	PB-700IB	PB-700IB	PB-700IB	PB-700IB	PB-700IB
	External dimensions(W/D/H)	mm	700/700/60	700/700/60	700/700/60	700/700/60	700/700/60	700/700/60
Panel	Shipping dimensions(W/D/H)	mm	740/740/115	740/740/115	740/740/115	740/740/115	740/740/115	740/740/115
	Net/Shipping weight	kg	2.8/4.5	2.8/4.5	2.8/4.5	2.8/4.5	2.8/4.5	2.8/4.5
	Wired(Optional)	/	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT	HW-BA101ABT
Controller		/	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B
		/	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK	HW-BA116ABK
		/	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
		/	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
	Infrared(Optional)	/	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01

