

# RoundWay CASSETTE



DC fan motor



Innovative 4 independent air flow control



Unique round-way air outlet, no blind spot



6 adjustable lower positions, 1296 air flow combinations



YR-E17A

YR-E16B

YR-HRS01

YR-HQS01

RoundWay  
CASSETTE

Model/Indoor unit			AB072MRERA	AB092MRERA	AB122MRERA	AB162MRERA	AB182MRERA	AB242MRERA	AB282MRERA	AB302MRERA	AB382MRERA	AB482MRERA	AB602MRERA
Capacity	Cooling	kBtu/h	7.5	9.5	12.3	15.3	19.1	24.2	27.3	30.7	38.2	47.7	54.6
		kW	2.2	2.8	3.6	4.5	5.6	7.1	8	9	11.2	14	16
Capacity	Heating	Btu/h	8.5	10.9	13.6	17.1	21.5	27.3	30.7	34.1	42.6	54.6	61.2
		kW	2.5	3.2	4	5	6.3	8	9	10	12.5	16	18
Electrical Parameters	Power supply	Ph/V/Hz	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60	1/220-230/50/60
Performance	Air flow (H)	m <sup>3</sup> /h	1000/810/620	1000/810/620	1000/810/620	1000/810/620	1000/810/620	1380/1190/1000	1380/1190/1000	2050/1860/1670	2050/1860/1670	2100/1910/1720	2100/1910/1720
	Sound pressure level(H/M/L)	dB(A)	30/27/25	30/27/25	30/27/25	32/29/27	33/30/29	35/34/31	37/35/31	37/35/31	44/40/36	44/40/36	44/40/36
Installation	External dimensions(W/D/H)	mm	840/840/180	840/840/180	840/840/180	840/840/180	840/840/180	840/840/204	840/840/204	840/840/246	840/840/246	840/840/288	840/840/288
	Shipping dimensions(W/D/H)	mm	983/983/268	983/983/268	983/983/268	983/983/268	983/983/268	983/983/290	983/983/290	983/983/331	983/983/331	983/983/373	983/983/373
	Net/Shipping weight	kg	25/28	25/28	25/28	25/28	25/28	27/30	27/30	31/36	31/36	33/38	33/38
	Refrigerant liquid pipe	mm	6.35	6.35	6.35	6.35	6.35	9.52	9.52	9.52	9.52	9.52	9.52
	Refrigerant gas pipe	mm	9.52	9.52	12.7	12.7	12.7	15.88	15.88	15.88	15.88	15.88	15.88
	Model name		PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)	PB-950KB/PB-950KB(H)
Panel	External dimensions(W/D/H)	mm	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50	950/950/50
	Shipping dimensions(W/D/H)	mm	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123	1013/1025/123
	Net/Shipping weight	kg	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9	6.5/9
	Wired(Optional)	/	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A	YR-E17A
Controller	Infrared(Optional)	/	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B	YR-E16B
		/	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01	YR-HQS01
		/	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01
		/	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01	YR-HRS01

