

2-Way CASSETTE



Compact design: only 220mm height



Ceiling antifouling design unique antifouling design



Built in high head drain pump



Quiet operation



HW-BA116ABK



YR-E17A



HW-BA101ABT



YR-E16B



YR-HRS01

*1. In case of using YR-HD alone, RE-02 needs to be purchased.

2. HW-BA116ABK, YR-E17A and HW-BA101ABT have built-in infrared signal receiver. YR-E16B no such function

2-Way CASSETTE

| | | | AB072MBERA | AB092MBERA | AB122MBERA | AB162MBERA | AB182MBERA |
|-----------------------|-----------------------------|-------------------|-----------------|-----------------|-----------------|-----------------|-----------------|
| Capacity | Cooling | kBtu/h | 7.5 | 9.6 | 12.3 | 15.4 | 19.1 |
| | | kW | 2.2 | 2.8 | 3.6 | 4.5 | 5.6 |
| | Heating | Btu/h | 8.5 | 10.9 | 13.6 | 17.1 | 21.5 |
| | | kW | 2.5 | 3.2 | 4 | 5 | 6.3 |
| Electrical Parameters | Power supply | Ph/V/Hz | 1/220-230/50/60 | 1/220-230/50/60 | 1/220-230/50/60 | 1/220-230/50/60 | 1/220-230/50/60 |
| | Air flow (H) | m ³ /h | 840/700/550 | 840/700/550 | 840/700/550 | 840/700/550 | 840/700/550 |
| Performance | Sound pressure level(H/M/L) | dB(A) | 42/37/33 | 42/37/33 | 42/37/33 | 44/39/34 | 44/39/34 |
| | Sound power level(H/M/L) | dB(A) | 55/50/46 | 55/50/46 | 55/50/46 | 57/52/47 | 57/52/47 |
| Installation | External dimensions(W/D/H) | mm | 817/620/220 | 817/620/220 | 817/620/220 | 817/620/220 | 817/620/220 |
| | Shipping dimensions(W/D/H) | mm | 1015/695/278 | 1015/695/278 | 1015/695/278 | 1015/695/278 | 1015/695/278 |
| | Net/Shipping weight | kg | 21/23 | 21/23 | 21/23 | 21/23 | 21/23 |
| | Refrigerant liquid pipe | mm | 6.35 | 6.35 | 6.35 | 6.35 | 6.35 |
| | Refrigerant gas pipe | mm | 9.52 | 9.52 | 12.7 | 12.7 | 12.7 |
| Panel | Model name | | P2B-1055IB | P2B-1055IB | P2B-1055IB | P2B-1055IB | P2B-1055IB |
| | External dimensions(W/D/H) | mm | 1055/680/68 | 1055/680/68 | 1055/680/68 | 1055/680/68 | 1055/680/68 |
| | Shipping dimensions(W/D/H) | mm | 1110/720/161 | 1110/720/161 | 1110/720/161 | 1110/720/161 | 1110/720/161 |
| | Net/Shipping weight | kg | 7/8 | 7/8 | 7/8 | 7/8 | 7/8 |
| Controller | Wired(Optional) | / | HW-BA101ABT | HW-BA101ABT | HW-BA101ABT | HW-BA101ABT | HW-BA101ABT |
| | | / | YR-E16B | YR-E16B | YR-E16B | YR-E16B | YR-E16B |
| | | / | HW-BA116ABK | HW-BA116ABK | HW-BA116ABK | HW-BA116ABK | HW-BA116ABK |
| | | / | YR-E17A | YR-E17A | YR-E17A | YR-E17A | YR-E17A |
| | Infrared(Optional) | / | YR-HRS01 | YR-HRS01 | YR-HRS01 | YR-HRS01 | YR-HRS01 |

